

# Chain Lube 1000 LM

Applied Lubrication Technology Inc. Chain Lube 1000 LM has been developed to meet the extreme lubrication demands of industry. This product acts as a lubricant, penetrant and cleaner that reaches all links, pins, and moving parts of a conveyor chain. The Chain Lube 1000 LM contains a unique blend of extreme pressure lubricating agents which greatly reduce chain wear and drive power consumption leading to increased chain life. In addition to these extreme pressure agents, the Chain Lube 1000 LM also contains molybdenum disulfide which deposits as a dry film coating on all metal surfaces. The molybdenum disulfide provides excellent anti-wear properties preventing metal to metal contact. This Chain Lube 1000 LM can be used in applications where temperatures can range from ambient up to 315°C (600°F).

Other unique qualities of the Chain Lube 1000 LM are its high corrosion protection, water-displacing, and acid atmosphere resistance properties enabling this lubricant to be used in the most severe and demanding industrial applications.

The Chain Lube 1000 is especially formulated to be applied by ALT's automated lubrication system.

## Technical Specification of Chain Lube 1000 LM:

Chain Lube 1000 LM	Typical Properties
Appearance	Dark Grey / Black
Odor	Mild Petroleum
Base Viscosity (of the concentrate portion)	142 cSt @ 40°C (667 sus@104°F)
	14.5 cSt @ 100°C (75 sus@212°F)
VI (Viscosity Index)	99
Flash Point (TCC)	47°C (117°F)
Copper Corrosion (ASTM D 130)	1 lb
Falex Test Load Lbs.	+1400
Specific Gravity @ 15.6°C (g/ml)	0.8047

## Product Applications

Although this product has been specifically developed for the lubrication of conveyor chains using a programmable automated application system, the Chain Lube 1000 LM can also be used for the lubrication of many different mechanical systems such as; Bearings, Gears, Sprockets, Hinges, Firearms, Linkages, Threads, Slides, Cables, Locking Mechanisms, and more.

## Product Packaging

Chain Lube 1000 LM is available in 18.9 Liter (5 Gallon) pails, 200 Liter (53 Gallon) drums, and 1200 Liter (317 Gallon) returnable tote bin quantities.

**Contact us for more information!**  
**Scan the qrcode to send us an email, we will contact you shortly.**



All reasonable care has been taken to ensure the information contained in this document is accurate as of the day of printing. However, such information may be affected by changes in the blend formulation occurring subsequent to the day of printing. Material Safety Data Sheets are available for all Applied Lubrication Technology Inc. products and must be consulted for appropriate storage, safe handling and disposal information of the product. Please contact us for more information. October 2012.