

# SA-E Series Electric Grease Pumps

## 12 VOLT DC GREASE PUMPS

These Battery Powered Pumps incorporate a unique solenoid drive that delivers unequalled performance from a small package, with extreme simplicity. These SA-E1 series pumps utilize a proven pump stem design for years of reliable service with simplified maintenance.

### ELECTRICAL SPECIFICATIONS:

Voltage - 12 VDC

Protection – 40 Amp Breaker

Connectors – 150 Amp CamLock

See below for various models with various dispense valve and meter options.



**All models come with cover assembly, follower plate, #6 x 10 ft. pos. & neg. cables with terminals**  
**Other flow rates and pressures available by special order - contact us for details.**

Model No.	Container	Maximum Operating Pressure	Flow Rate Cu. In./Min
SA-E1-P40	17 KG (35 LB.) PAIL	4,000	14.0
SA-E1-P50	17 KG (35 LB.) PAIL	5,000	10.0
SA-E1-K40	55 KG (120 LB.) KEG	4,000	14.0
SA-E1-K50	55 KG (120 LB.) KEG	5,000	10.0

**WARNING:**

Equipment contained in this catalog can generate very high fluid pressure. To reduce the risk of serious bodily injury or property damage, never exceed the maximum working pressure of the lowest rated system component.

Before each use, make sure all components are in place, are in safe operating condition and operating properly.

Do not alter or modify any part of the equipment as this may cause or result in serious bodily injury, including injecting fluid or grease through the skin or splashing in the eyes. To reduce the risk of serious bodily injury or property damage. Always read and follow the manual included with the equipment for more detailed information.