

SA-E Series Electric Grease Pumps

115/230 VOLT AC GREASE PUMPS

Unique cam drive allows unequalled performance from a small package, with extreme simplicity. This new series utilizes a proven pump stem design for years of reliable service with simplified maintenance.

Models available with vent valve installed for automatic parallel systems, and with a variety of electrical connectors for interfacing with a PLC or controller.

ELECTRICAL SPECIFICATIONS:

Voltage - 115/230 AC

Amps – 2.4 / 1.2

Motor – ¼ H.P., TEFC, PSC

See below for various models with various dispense valve and meter options.



SA-E3-K50

All models come with cover assembly and follower plate.
Other pressures and flow rates available by special order - contact us for details.

Model No.	Container	Maximum Operating Pressure	Flow Rate Cu. In./Min
SA-E3-P35	17 KG (35 LB.) PAIL	3,500	3.8
SA-E3-P50	17 KG (35 LB.) PAIL	5,000	6
SA-E3-P75	17 KG (35 LB.) PAIL	7,500	8.7
SA-E3-K35	55 KG (120 LB.) KEG	3,500	3.8
SA-E3-K50	55 KG (120 LB.) KEG	5,000	6
SA-E3-K75	55 KG (120 LB.) KEG	7,500	8.7

WARNING:

Equipment contained in this catalog can generate very high fluid pressure. To reduce the risk of serious bodily injury or property damage, never exceed the maximum working pressure of the lowest rated system component.

Before each use, make sure all components are in place, are in safe operating condition and operating properly.

Do not alter or modify any part of the equipment as this may cause or result in serious bodily injury, including injecting fluid or grease through the skin or splashing in the eyes. To reduce the risk of serious bodily injury or property damage. Always read and follow the manual included with the equipment for more detailed information.