



Air-Operated Oil Dispensers

6.4 gal

17.2 gal

Air-operated oil dispensers suitable for high-viscosity oil.

Filled with oil to 4/5 their capacity and pressurized to 90 - 120 psi, they work independently without requiring connection to the compressed air system. The air-operated oil dispensers are ideal for filling or topping-up engine, gearbox, differential, hydraulic power pack, reduction unit oil, etc.



Do not use flammable or corrosive liquids

P/N 33024-55

Air-operated oil dispenser with wheel-mounted 6.4 gal tank equipped with:

- level gauge
- delivery handle with flexible terminal
- P/N 24891-55 antispash funnel

P/N 33025-55

Air-operated oil dispenser with wheel-mounted 6.4 gal tank equipped with:

- level gauge
- delivery handle with flexible extension suitable for ATF (Mercedes connections) and electronic meter (P/N 37780-55)
- P/N 24891-55 funnel

P/N 33065-55

Air-operated oil dispenser with wheel-mounted 17.2 gal tank equipped with:

- level gauge
- P/N 37738-55 delivery control handle
- P/N 24891-55 funnel

P/N 33066-55

Air-operated oil dispenser with wheel-mounted 17.2 gal tank equipped with:

- level gauge
- P/N 37739-55 delivery control handle with flexible extension
- P/N 24891-55 funnel

Packaging - Weight

No. 1 3.0 ft³ lb 30

No. 1 3.0 ft³ lb 32

No. 1 6.5 ft³ lb 54

No. 1 6.5 ft³ lb 57

