



Electronic Meters - Antifreeze & Deisel



P/N 33710-55

P/N 33711-55

P/N 37785-55

Flow rate	23.8 gpm
Compatible fluids	diesel fuel
Body's material	aluminum
Gear's material	POM
Inlet	3/4" NPT (f)
Outlet	3/4" NPT (f)
Max operating pressure	1015 psi
Burst pressure	2900 psi
Accuracy	± 0.3 %
Net weight	2 lb
Overall dimensions (A - B - C)	3.7" - 3.6" - 3.0"
Packaging - Weight	No. 1 0.1 ft ³ lb 2

Flow rate	31.7 gpm
Compatible fluids	diesel fuel
Body's material	aluminum
Gear's material	POM
Inlet	1" NPT (f) + Flange
Outlet	1" NPT (f) + Flange
Max operating pressure	1015 psi
Burst pressure	2900 psi
Accuracy	± 0.3 %
Net weight	2.4 lb
Overall dimensions (A - B - C)	4.3" - 3.6" - 3.9"
Packaging - Weight	No. 1 0.2 ft ³ lb 3

Flow rate	10.5 gpm
Compatible fluids	antifreeze and windshield washing fluid
Body's material	oxidized aluminum (zancofuso®)
Gear's material	PVDF
Inlet	1/2" NPT (f)
Outlet	1/2" NPT (f)
Max operating pressure	1015 psi
Burst pressure	2900 psi
Accuracy	± 0.3 %
Net weight	1 lb
Overall dimensions (A - B - C)	3.7" - 3.5" - 2.3"
Packaging - Weight	No. 1 0.05 ft ³ lb 1.9

