



Electronic Meters

RAASM's electronic meters, besides gauging the liquid delivered, can show instant flow rates, provide a reset total and allow the setting of different units of measurement. RAASM's electronic meters are suitable for a wide variety of fluids, from low to medium to high viscosities, including lubricants, diesel fuel, antifreeze, window wash liquid and other fluids compatible with the material of the meter.



P/N 37780-55

P/N 37781-55

P/N 37782-55

Flow rate	9.25 gpm
Compatible fluids	oil and similar
Body's material	aluminum
Gear's material	POM
Inlet	1/2" NPT (f)
Outlet	1/2" NPT (f)
Max operating pressure	1015 psi
Burst pressure	2900 psi
Accuracy	± 0.3 %
Net weight	1 lb
Overall dimensions (A - B - C)	3.7" - 3.5" - 2.2"
Packaging - Weight	No. 1 0.05 ft ³ lb 1.9

Flow rate	18.5 gpm
Compatible fluids	oil and similar
Body's material	aluminum
Gear's material	POM
Inlet	3/4" NPT (f)
Outlet	3/4" NPT (f)
Max operating pressure	1015 psi
Burst pressure	2900 psi
Accuracy	± 0.3 %
Net weight	2 lb
Overall dimensions (A - B - C)	3.7" - 3.6" - 3.0"
Packaging - Weight	No. 1 0.06 ft ³ lb 2.2

Flow rate	26.42 gpm
Compatible fluids	oil and similar
Body's material	aluminum
Gear's material	POM
Inlet	1" NPT (f) + Flange
Outlet	1" NPT (f) + Flange
Max operating pressure	1015 psi
Burst pressure	2900 psi
Accuracy	± 0.3 %
Net weight	2.4 lb
Overall dimensions (A - B - C)	4.3" - 3.6" - 3.9"
Packaging - Weight	No. 1 0.2 ft ³ lb 3

