



# Hot Water Hose Reels - 3000 PSI



Hose reels with hoses in black synthetic rubber and zinc plated steel fittings.



The hose reels are equipped with a universal hose stop; those with hose are provided with a 2' inlet connection hose.

Seals are in **Viton®**  
Seals are in **Teflon®** for water 5800 psi  
Swivel joint in **Stainless Steel**

	P/N	P/N	Delivery hose			Inlet connection	Outlet connection
	PAINTED STEEL	AISI 304 STAINLESS STEEL	ø	length	P/N hose		
<b>Series 330</b>	8330.300-55	8332.300-55	without hose			3/8" NPSM (f)	3/8" NPTF (f)
	8330.301-55	-	5/16"	40'	994.512-55	3/8" NPTF (m)	3/8" NPTF (f)
<b>Series 390</b>	8390.300-55	8392.300-55	without hose			3/8" NPSM (f)	3/8" NPTF (f)
	8390.301-55	-	5/16"	40'	994.512-55	3/8" NPTF (m)	3/8" NPSM (f)
	8390.302-55	-	5/16"	56'	994.517-55	3/8" NPTF (m)	3/8" NPSM (f)
<b>Series 430</b>	8430.300-55	8434.300-55	without hose			3/8" NPSM (f)	3/8" NPSM (f)
	8430.301-55	-	3/8"	40'	995.512-55	3/8" NPTF (m)	3/8" NPSM (f)
	8430.302-55	-	3/8"	60'	995.518-55	3/8" NPTF (m)	3/8" NPSM (f)
<b>Series 530</b>	8530.300-55	8534.300-55	without hose			3/8" NPSM (f)	3/8" NPSM (f)
	8530.301-55	-	3/8"	65'	995.520-55	3/8" NPTF (m)	3/8" NPSM (f)
	8530.302-55	-	3/8"	80'	995.525-55	3/8" NPTF (m)	3/8" NPSM (f)
<b>Series 530</b> 5800 psi	8530.350-55	8534.350-55	without hose			3/8" NPSM (f)	3/8" NPSM (f)
<b>Series 540</b>	8540.300-55	8544.300-55	without hose			3/8" NPSM (f)	3/8" NPSM (f)
	8540.301-55	-	3/8"	100'	995.530-55	3/8" NPTF (m)	3/8" NPSM (f)
<b>Series 560</b>	8560.300-55	8564.300-55	without hose			3/8" NPSM (f)	3/8" NPSM (f)
	8560.301-55	-	3/8"	130'	995.540-55	3/8" NPTF (m)	3/8" NPSM (f)
	8560.302-55	-	3/8"	165'	995.550-55	3/8" NPTF (m)	3/8" NPSM (f)

