



Series 238 - 1:1 - 600

Series 238 air-operated pumps for short and medium distance transfer. Ideal for transferring low-viscosity fluids such as: waste oils (filtered), lubricants, antifreeze and diesel fuel. The wall-mount version of these pumps is also available with special accessories and/or extensions for specific applications

COMPATIBLE FLUIDS

- MO** Low and medium viscosity fluids
- WO** Waste fluids
- AD** Antifreeze, diesel fuel



P/N 33061-55

P/N 33096-55

P/N 33071-55

P/N 33073-55

	P/N 33061-55	P/N 33096-55	P/N 33071-55	P/N 33073-55
Type of seals	Teflon®	Teflon®	Viton®	Viton®
Air motor	aluminum	aluminum	aluminum	aluminum
Suction tube	carbon steel	carbon steel	carbon steel	carbon steel
Bung adapter	38042	38042	38042	38042
Air inlet connection	1/4" NPT (f)	1/4" NPT (f)	1/4" NPT (f)	1/4" NPT (f)
Fluid outlet connection	1/2" NPT (f)	1/2" NPT (f)	1/2" NPT (f)	1/2" NPT (f)
Air working pressure	90 - 120 psi	90 - 120 psi	90 - 120 psi	90 - 120 psi
Noise level	81 dB	81 dB	81 dB	81 dB
Deliverable oil temperature	14 - 122 °F	14 - 122 °F	14 - 122 °F	14 - 122 °F
Max. deliverable oil viscosity	80 SAE	80 SAE	80 SAE	80 SAE
Cycles per gallon	39.1	39.1	39.1	39.1
Max. air consumption 120 psi	13 cfm	13 cfm	13 cfm	13 cfm
Suction tube length	9.8" (excluded P/N 10/20-55)	37"	9.8" (excluded P/N 10/20-55)	37"
Suction tube external diameter	ø 1.65"	ø 1.65"	ø 1.65"	ø 1.65"
Type of installations	modular - customizable 1"	suitable for drum 55 gal	modular - customizable 1"	suitable for drum 55 gal
Packaging - Weight	No. 1 0.35 ft³ 11 lb	No. 1 0.60 ft³ 13 lb	No. 1 0.35 ft³ 11 lb	No. 1 0.60 ft³ 13 lb

