



Series 238 - 3:1 - 4.40 gpm

**Series 238
air-operated pumps
for medium-distance
oil distribution.**

Ideal for distributing medium viscosity oils. Suitable for movable installations and fixed systems.

The wall-mount version of these pumps is also available with special accessories and/or extensions for specific applications.

COMPATIBLE FLUIDS

MO Low and medium viscosity fluids



P/N 35561-55

P/N 35564-55

P/N 35567-55

| | |
|--------------------------------|-------------------------------|
| Type of seals | NBR |
| Air motor | aluminum |
| Suction tube | carbon steel |
| Bung adapter | 38042-55 |
| Air inlet connection | 1/4" NPT (f) |
| Fluid outlet connection | 1/2" NPT (f) |
| Air working pressure | 90 - 120 psi |
| Noise level | 81 dB |
| Deliverable oil temperature | 14 - 122 °F |
| Max. deliverable oil viscosity | 130 SAE |
| Cycles per gallon | 102.3 |
| Max. air consumption 120 psi | 26 cfm |
| Suction tube length | 10.7" (excluded P/N 10/20-55) |
| Suction tube external diameter | 1.65" |
| Type of installations | modular - customizable 1" |
| Packaging - Weight | No. 1 0.35 ft³ lb 12 |

| | |
|--------------------------------|--------------------------|
| Type of seals | NBR |
| Air motor | aluminum |
| Suction tube | carbon steel |
| Bung adapter | 38042-55 |
| Air inlet connection | 1/4" NPT (f) |
| Fluid outlet connection | 1/2" NPT (f) |
| Air working pressure | 90 - 120 psi |
| Noise level | 81 dB |
| Deliverable oil temperature | 14 - 122 °F |
| Max. deliverable oil viscosity | 130 SAE |
| Cycles per gallon | 102.3 |
| Max. air consumption 120 psi | 26 cfm |
| Suction tube length | 29" |
| Suction tube external diameter | 1.65" |
| Type of installations | suitable for drum 16 gal |
| Packaging - Weight | No. 1 0.49 ft³ lb 14 |

| | |
|--------------------------------|--------------------------|
| Type of seals | NBR |
| Air motor | aluminum |
| Suction tube | carbon steel |
| Bung adapter | 38042-55 |
| Air inlet connection | 1/4" NPT (f) |
| Fluid outlet connection | 1/2" NPT (f) |
| Air working pressure | 90 - 120 psi |
| Noise level | 81 dB |
| Deliverable oil temperature | 14 - 122 °F |
| Max. deliverable oil viscosity | 130 SAE |
| Cycles per gallon | 102.3 |
| Max. air consumption 120 psi | 26 cfm |
| Suction tube length | 37" |
| Suction tube external diameter | 1.65" |
| Type of installations | suitable for drum 55 gal |
| Packaging - Weight | No. 1 0.60 ft³ lb 16 |

