



# Series 238 - 50:1 - 3.3 lb/m

**Series 238**  
**air-operated pumps**  
**for short/long distance**  
**grease distribution,** for  
 high pressure greasing.  
 Ideal for dispensing  
 medium/high-viscosity  
 grease. Suitable for  
 mobile installations and  
 centralized fixed systems.



**P/N 62141-55**

**P/N 62148-55**

**P/N 62174-55**

**P/N 62195-55**

Type of seals	polyurethane
Suction tube upper body	aluminum
Suction tube	carbon steel
Air inlet connection	1/4" NPT (f)
Grease outlet connection	1/4" NPT (f)
Cycles per lb	136
Air working pressure	90 - 120 psi
Max. air consumption 120 psi	26 cfm
Noise level	81 dB
Max. deliverable grease viscosity	NLGI 2
Suitable for drums	35 lb
Suction tube length	16"
Suction tube external diameter	ø 1.18"
Type of installations	for small drum
Packaging - Weight	No. 1 0.35 ft <sup>3</sup> lb 11

Type of seals	polyurethane
Suction tube upper body	aluminum
Suction tube	carbon steel
Air inlet connection	1/4" NPT (f)
Grease outlet connection	1/4" NPT (f)
Cycles per lb	136
Air working pressure	90 - 120 psi
Max. air consumption 120 psi	26 cfm
Noise level	81 dB
Max. deliverable grease viscosity	NLGI 2
Suitable for drums	35 lb
Suction tube length	19"
Suction tube external diameter	ø 1.18"
Type of installations	for small drum
Packaging - Weight	No. 1 0.35 ft <sup>3</sup> lb 11

Type of seals	polyurethane
Suction tube upper body	aluminum
Suction tube	carbon steel
Air inlet connection	1/4" NPT (f)
Grease outlet connection	1/4" NPT (f)
Cycles per lb	136
Air working pressure	90 - 120 psi
Max. air consumption 120 psi	26 cfm
Noise level	81 dB
Max. deliverable grease viscosity	NLGI 2
Suitable for drums	120 lb
Suction tube length	29"
Suction tube external diameter	ø 1.18"
Type of installations	suitable for drum 120 lb
Packaging - Weight	No. 1 0.52 ft <sup>3</sup> lb 14

Type of seals	polyurethane
Suction tube upper body	aluminum
Suction tube	carbon steel
Air inlet connection	1/4" NPT (f)
Grease outlet connection	1/4" NPT (f)
Cycles per lb	136
Air working pressure	90 - 120 psi
Max. air consumption 120 psi	26 cfm
Noise level	81 dB
Max. deliverable grease viscosity	NLGI 2
Suitable for drums	400 lb
Suction tube length	37"
Suction tube external diameter	ø 1.18"
Type of installations	suitable for drum 400 lb
Packaging - Weight	No. 1 0.65 ft <sup>3</sup> lb 16

