



# Series 238 Stainless Steel 1:1 8 gpm

**AISI 304 stainless steel air-operated pumps** for short/medium distance transfer. Ideal for transferring low/medium-viscosity fluids such as: antifreeze liquid, windshield washing liquid, DEF and chemical products.

- DE** DEF (Diesel Exhaust Fluid)
- AD** Antifreeze, diesel fuel
- WF** Windshield fluid



### P/N 33360-55

### P/N 33396-55

### P/N 33363-55

Type of seals	Viton®
Air motor	stainless steel AISI 304 - Aluminum
Suction tube	stainless steel AISI 304
Air inlet connection	1/4" NPT (f)
Fluid outlet connection	1/2" NPT (f)
Cycles per gallon	48.2
Air max. pressure	120 psi
Noise level	81 dB
Deliverable oil temperature	14 - 122 °F
Bung adapter	-
Suction tube length	-
Suction tube external diameter	-
Max. air consumption 120 psi	13 cfm
Type of installations	modular
Packaging - Weight	No. 1 0.4 ft³  lb 12

Type of seals	Viton®
Air motor	stainless steel AISI 304 - Aluminum
Suction tube	stainless steel AISI 304
Air inlet connection	1/4" NPT (f)
Fluid outlet connection	1/2" NPT (f)
Cycles per gallon	48.2
Air max. pressure	120 psi
Noise level	81 dB
Deliverable oil temperature	14 - 122 °F
Bung adapter	P/N 33434-55
Suction tube length	37"
Suction tube external diameter	ø 1.34"
Max. air consumption 120 psi	13 cfm
Type of installations	suitable for drum 55 gal
Packaging - Weight	No. 1 0.7 ft³  lb 16

Type of seals	Viton®
Air motor	stainless steel AISI 304 - Aluminum
Suction tube	stainless steel AISI 304
Air inlet connection	1/4" NPT (f)
Fluid outlet connection	1/2" NPT (f)
Cycles per gallon	48.2
Air max. pressure	120 psi
Noise level	81 dB
Deliverable oil temperature	14 - 122 °F
Bung adapter	P/N 33434-55
Suction tube length	49.6"
Suction tube external diameter	ø 1.34"
Max. air consumption 120 psi	13 cfm
Type of installations	for IBC
Packaging - Weight	No. 1 0.7 ft³  lb 20

