



Waste Oil and Antifreeze Drains

Waste oil and antifreeze drains with wheel-mounted tank.

Suitable for gravity draining of engine, gearbox differential oil and antifreeze from all motor vehicles placed on an auto lift or pit.

The bowl with height-adjustable is mounted on a swivel joint that facilitates positioning.



Do not use flammable or corrosive liquids

P/N 42085-55

Waste oil drainer with wheel-mounted 21.1 gal tank, equipped with:

- level gauge
- 4.2 gal collection bowl
- antispash screen/filter
- removable tool tray

Tank capacity	21.1 gal
Max. collection capacity	16.4 gal
Bowl capacity	4.2 gal
Oversize funnel diameter	ø 17.1"
Draining hose length	7'
Max. height	69.3"
Min. height	56.7"
Draining pressure	7 psi
Packaging - Weight	No. 1 6.7 ft ³ lb 73

P/N 42090-55

Waste oil drainer with wheel-mounted 23.8 gal tank, equipped with:

- level gauge
- 3.9 gal collection bowl with oversize funnel
- antispash screen/filter
- removable tool tray

Tank capacity	23.8 gal
Max. collection capacity	19.8 gal
Bowl capacity	3.9 gal
Oversize funnel diameter	ø 22.9"
Draining hose length	7'
Max. height	74.9"
Min. height	55.2"
Draining pressure	7 psi
Packaging - Weight	No. 2 10.6 ft ³ lb 75

